

model series: HYMAR-6U(L)-2.3R(G,Y,B)
Smaller Upper or Lower Seconds

FLUSH / SURFACE MOUNT

RED, GREEN, YELLOW, BLUE

STANDARD FEATURES:

- * Infra Red hand held REMOTE CONTROL for all functions
- * 12 or 24 Hour and Military Display Format (user selectable via remote)
- * Stand - Alone operation for Home or Office
- * Backup:
Self-recharging backup - NO BATTERY NEEDED
- * Day/Date/Month/Year Alternating display selection
- * Fully Adjustable Brightness (Manual via remote control)
- * Julian Day display
- * Auto Leap-Year correction
- * Day Light Savings correction
- * Timers:
Wake-Up Alarm Timer with soft beeper control
Stop-Watch function up to 1/100 sec resolution
Up/Down Presettable Timer and Counter with Alarm (up to 99hrs:59min:59sec or 999999 counts)
Cycling timer, Up and Down
- * On-Board Alarms: Internal Alarm buzzer
- * NON-GLARE lens
- * NON-MULTIPLEXING - Camera friendly
- * Variety of enclosure colors.

Surface Mount (or optional Flush Mount)
Water-Proof , Shock-Proof Enclosure
Stainless Steel painted with baked enamel



Multifunction
Remote Control
Included

SPECIFICATIONS:

Supply Voltage:	115V, 208-240V, 50/60Hz 24 or 12V AC/DC
Power:	6VA average
Operating Temperature:	-20C to +70C (-4F to 158F)
Dimensions (w/o back flange)	15" x 5" x 2.5" (38.1cm x 12.7cm x 6.3cm)
Back Flange:	Add 0.5" (1.27cm) on each side and depth
Visibility:	Up to 80Ft. (25m)



Optional FEATURES:

- * Direct Replacement for existing MASTER - SLAVE SYSTEM CLOCKS (replaces round, mechanical or electronic)
- * Multiple Master-Slave correction modes:
Master-Slave Power Line Carrier sync (Simplex)
Master-Slave 2 Wire, RS485 Twisted Pair Sync/Communication
Master-Slave wireless communication on power line wiring
Master-Slave wireless RF, radio communication
Master-Slave network ethernet communication
Master-Slave BCD digital, ASCII Time Code
RS232, USB and RS485 serial communication (PC port as the Master)
Master-Slave 2 and 3 Wire, 24V Minute Impulse Sync
- * Multi-Zone synchronized Master-Slave system
- * Temperature Monitoring and Control:
Multi-Event Programmable Thermostat (up to 32 events/day)
Heating - Cooling Auto Change-Over
Inside and Outside Thermometer function
Min/Max Temperature Memory
Temperature Alarm and Relay outputs (up to 2 x Form C, 10Amp/250V)
- * Backup:
10 Year Lithium battery option
- * Atomic Clock radio option (WWWVB60, DCF77, HBG75, MSF60, OHTAKADOYA40, HAGANE60)
- * Atomic Clock GPS option
- * Automatic Brightness with Auto-dimming option
- * Timers:
Multi-Event Programmable Timer (up to 32 events/day)
Stop-Watch function up to 1/100 sec resolution
External Start/Stop/Reset switch inputs
Auto-reloading time period measurement
Continuous time count on power failure
- * On-Board Alarm Relays for timers and counters:
(up to 2 x Form C, 10Amp/250V) For external load, siren or horn.

**Enclosure series 732S23WP and 723SX23WP (or 732S23FLWP and 723SX23FLWP)
Straight 6-digit model (standard colors: grey, black, white)**



Model with internal power supply

Enclosure series 732S23WP




Model with external power supply


Enclosure series 732SX23WP



Permanent flush mounting with hidden bolts



Flush mounting with retaining springs



Permanent surface mounting with hidden bolts

